

4port/8port/16Port Combo KVM Switch over IP



Main feature :

With 4ports/8ports/16ports in 1U

- Support all computers to both boot and hot-swappable.
- Cascade switches up to 4/8/16 levels and Mix switches DB-15 KVM
- Mix PS/2,USB,SUN & MAC with Multi-Platform switch capability
- Auto scan for monitoring PCs ,easy select via push buttons, Hot keys, OSD Hot Pluggable, no software or drivers required
- Easy & quick installation.

Introduction

- Support hot plug and play, Increase the PC, or move the PC-link for maintenance without turning off the KVM or PC power supply.
- Resolution:2048x1536, Bandwidth:75Hz
- It can be very simple to use OSD, buttons and hotkeys to select the computer without any software.
- Support 8-character password protection and the search of the PC server.
- Using the isolation technology and simulation technology on the name, to avoid the crosstalk between keyboard and mouse.
- Rackmount (Height: 1U, 19" standard).
- Auto Scan Mode and flexible scan time mode (1~255 sec.)
- There is a buzzer sound if the keyboard is connected to PC successfully and resumes the original state.
- Using the standard keyboard, VGA cable and Mouse.
- Built-in tandem ports don't waste any PC port.

- Auto-detection equipment, which can customize hotkeys
(Scroll-Lock/Cap-Lock/Num-Lock/Alt/Ctrl/Win).
- Avoid hot-key repeat with the other KVM or the machine.
- Supports two-password security protection and the name search of the computer.

Specification

Model	4 ports	8 ports	16 ports
computer connection (Direct)	4	8	16
computer connection (Max.)	128	256	512
connection port	Control port: Display、Keyboard&Mouse.		
	PC port: USB cable; LAN port;		
OSD Switch	Support		
Switch mode	Hotkey		
	OSD menu		
Switch scan time	1~255 Sec.（adjustable by OSD）		
LAN Port	10/100Mb		
Pre-electronic Key	To select the appropriate server through electronic keys		
Input	AC 100V-240V 47-63Hz Power: 1W		
Cabinet Material	High strength and anti-corrosive rigid plate		
Color	Insulated black paint (optional)		
Dimension	180mm*438mm*44mm		
Weight	4.65KG	6.55KG	8.45KG
For cabinet	All		
Environment	Storage Temp	-30℃~65℃	
	Operating Temp	-10℃~60℃	
	Humidity	0%~80% RH	
Safety Certification	CCC /FCC/ CE		
Type	19" Rack mount KVM Switch		
Port	1*VGA monitor; 1 *LAN; 1*PS / 2 Keyboard; 1* PS / 2 Mouse.		
PC support	15 Pin VGA Port (female) 6 Pin PS/2 Keyboard (female) 6 Pin PS/2 Mouse (female) 1 10/100 M Lan port		