



RIS1701S: is a single rail 17" Monitor, Keyboard-Drawer with LED Backlight. It integrates a single port VGA KVM switch, monitor, keyboard & mouse into 1U height and is used to control one computer. A value keyboard with number block and the integrated touchpad are completing the external design. The housing conforms the 1U standard, is easily installed and mountable with the included mounting kit.

Depth: 410mm (without handle)

FEATURES:

- * Front LCD Console + DB 37 pins cable in short total length 410mm, supports PS.2/USB
- * Can be connected with different KVM modules, for example with 8/16 ports (VGA/CAT5)
- * an USB 1.1 port on the front side, for external mouse or keyboard
- * high and clear resolution 1280 x 1024 (60Hz)

KEYBOARD VERSIONS:

Available in following versions: German (DE), US-English (US), British-English (UK), French (FR), Spanish (SP), Italian (IT), Turkish (TR), Swedish/Finnish (SWE/FI), Swiss (CH) and Russian (RU)

SPECIFICATIONS:

| Type | | RIS1701S |
|----------------------------------|--|---|
| Computer Connection (direct/max) | | 1 |
| CPU Port Selection | | -- |
| IP Remote Control | | No -- |
| LCD monitor | Monitor type | 17" SXGA color TFT-LCD |
| | Ratio | 4:3 |
| | Visible square | 337.920(H) x 270.336 (V)mm |
| | Resolution(max) | 1280 x 1024 60Hz |
| | Support Color | 16.7M colors (RGB 6-bit +Hi-FRC) |
| | White Luminance | 250 cd/m2 (Typ.) |
| | contrast | 1000:1 (Typ) |
| | Back light | LED |
| | Pixel Pitch | 0.264 x 0.297 (per one triad) x 0.3 |
| | LCD MTBF | 1000,000 hours |
| | Input power | DC 12 V |
| Connectors | DB 37pin Rear* | 1 x PS/2 female (purple, green) |
| | | 1x Kombi-USB |
| | | 1 x HDB-15 VGA male (blue) |
| USB Front | 1 x USB for external mouse or keyboard | |
| Keyboard | Keyboard | Standard 100keys (10 different languages for choose) |
| | Compatible IBM/AT | Win Series/Server 2008/Server 2013/Linux, MacOS, etc. |
| | Using life | >1,000,000 times |
| Mouse | Type | Touch Pad |
| | X/Y resolution | >1000dots/inch (40x40/mm) |
| | Using life | >1,000,000 times |
| Power | Power (AC) | ~100V-240V |
| | Using life | MTBF >60,000hours 25 °C |
| Housing | | Metal (black) |
| Rail system | | Single Rail |
| Gross weight | | 15.0 kg |
| Dimensions (installation depth) | | 407.5 x 450 x 44.5mm |
| Dimensions (with handle) | | 462.6 x 450 x 44.5mm |
| Rack installation depth | | 410mm - 900mm (min/max adjustable) |
| Operating / Storage Temp | | -10 - 50°C / -20 - 60°C |